

diagonal $N 88^{\circ} E$ 28 links distant corner made 87. poles 12
links south of the center Hickory 5 inches diameter $N 32^{\circ} E$
7 links distant white oak 5 inches diameter $N 72^{\circ} E$ 9
links distant corner made at (R) the center of south
west quarter of section no 32, white walnut 18 inches diam
 $S 77^{\circ} E$ 41 links distant white oak 15 inches diameter $N 24^{\circ} E$
44 1/2 links distant length of the line from A to A 80. poles
length from A to B. 80. poles length of the line west of the
center 159. poles 17. links. length of the line from from
the corner standing 1/4 mile west of the Eastern 1/2 mile
part of section no 32) 241. poles 20 links to (g)

chain bearers in section 32. Thomas Peter son John
A Polley James Polley & Joseph Polley (Jr) sworn
this March 3^d A.D. 1859.

James W. Spencer
Monroe County Surveyor

April 25th A.D. 1859.

ran the following lines and made the following corners
in section no 18 Township no 8 North of range no 1 East
for Henderson Ellis John C. Johnston John Garrison & Joseph
Shields beginning at a stone standing at the S E corner of
the $N 1/4$ of $N E$ quarter of section no 18. witness trees Buck
30 inches diameter $S 57^{\circ} E$ 15 1/2 links dist Dogwood 5 in diam
 $N 67^{\circ} E$ 32 1/2 links dist thorn $S 6^{\circ} E$ 154 poles 18 links to a stone
at the $N E$ cor of $S 1/4$ of $S E$ quarter of said section (18
witness Buck 18 in diameter $S 1^{\circ} E$ 6 links dist Maple 12
inches diam $N 20^{\circ} E$ 13. links distant

James Ellis and John Armstrong chain bearers by
consent of Parties

James W. Spencer
Monroe County Surveyor.